



# Stat Fax<sup>®</sup> 1904Plus - Chemistry Analyzer

Inset - shown with Mosquito<sup>®</sup> Aspiration Flow Cell accessory

## Features

- ⇒ Bichromatic optical system with six wavelengths including 340nm.
- ⇒ Pre-programmed calculations for both kinetic and endpoint assays.
- ⇒ Twelve-station 37°C incubation block and temperature-controlled read cell.
- ⇒ Easy to use with step-by-step prompting and built-in thermal printer with graphics capability.
- ⇒ Large, non-volatile memory to store more than 50 curves and test parameters.

## Options & Accessories

- ⇒ Redi-Check<sup>®</sup> to monitor accuracy, linearity, and repeatability of Stat Fax<sup>®</sup> Chemistry Analyzer.

## Mosquito<sup>®</sup> Aspiration Flow Cell

- ⇒ Powered from the Stat Fax<sup>®</sup> Chemistry Analyzer.
- ⇒ Keyboard selectable read volume from 250mL to 500 mL.
- ⇒ Software controlled with user prompts.
- ⇒ Internal extra-quiet vacuum pump.
- ⇒ All cables and connectors included.

**Distributed by:**



AWARENESS TECHNOLOGY, Inc. PO Box 1679, Palm City, FL 34991 (772) 283 6540 fax (772) 283 8020  
 web: <http://www.awaretech.com> email: [info@awaretech.com](mailto:info@awaretech.com)

*Cost Effective by Design<sup>®</sup>*

# Stat Fax<sup>®</sup> 1904 Chemistry Analyzer Specifications

## Photometric

Linear Measurement Range:	0.0 to 2.5 Absorbance units (A).
Photometric Accuracy:	+/- (1% of the reading + 0.005A).
Stability:	Drift of no more than 0.005A in 8 hours/bichromatic.
Light Source:	Tungsten lamp with lamp saver feature.
Standard Wavelengths:	340, 405, 450, 505, 545 and 600nm. (alternate filters available from 340 to 700nm)
Filter Type:	IAD hardcoat interference, 10nm half bandpass.
Tube Size:	12 mm round is standard.
Minimum sample volume:	1mL for 12mm round tube, 250mL with Mosquito accessory.

## Electronic

Display:	Alphanumeric, 16 character LCD.
Printer:	Thermal dot matrix, 20 characters per line, plus graphics.
Keyboard:	16-key, domed membrane switch, enunciating.
Power Requirements:	115V or 230V AC, 50-60Hz (switch selectable).

## Software

Speed:	Reads, calculates and prints results - 3 seconds per tube.
Calculation Modes:	Single point calibration by standard or factor, multipoint calibration with point-to-point curve fit, rate by standard or factor (batch or singly).
Test Menu:	More than 60 open channels to store tests. Stores all parameters including wavelengths, calculations, unit codes, linear and normal ranges, rate timing, standard values, test names, and previous standard curve.

## Other

Temperature	37°C, block stays on, cell has on/off switch.
Enclosure:	Painted flame-retardant ABS plastic cover with metal base.
Dimensions:	Approx. 9x13.5x5in. (24x34x13cm) weighs 10 lbs.(4.5kg).
Certifications:	NRTL listed, CE mark.

## Mosquito<sup>®</sup> Aspiration Flow Cell specifications

### Cell

Minimum aspiration volume:	250mL at 7"Hg vacuum.
Other Volume Options:	300, 350, 400, 450, 500mL.
Illuminated Volumes:	21mL.
Equivalent Pathlength:	1cm.
Cell Body:	Surgical grade stainless.
Windows:	1mm Pyrex.

### Control Module

Power Input:	12V DC/0.7A from analyzer.
Valve:	Silicone pinch type.
Vacuum Sensor:	Piezoresistive bridge type.
Vacuum Regulation:	Better than 0.25" Hg.
Vacuum Pump:	Self contained.
Full Sensor:	Stainless conductivity probe.

Mosquito<sup>®</sup> is compatible with 1900 series chemistry analyzers with 12mm round read cell manufactured by Awareness Technology, Inc.